

## PRODUCT SPECIFICATION

<b>Floor type</b>	multi-layer rigid vinyl flooring with click system			
<b>Collection</b>	<b>Wood</b>	<b>Herringbone</b>	<b>Wood+</b>	<b>Herringbone+</b>
<b>Format</b>	plank	herringbone	plank	herringbone
<b>Overall thickness</b>	ISO 24337	5 mm		6 mm
<b>Wear layer</b>	EN 429	0,30 mm		0,55 mm
<b>Plank/tile size</b>	ISO 24337	180 x 1220 mm	125 x 625 mm	180 x 1220 mm 125 x 625 mm
<b>Total weight</b>	ISO 23997	8400 g/m <sup>2</sup>	8200 g/m <sup>2</sup>	9500 g/m <sup>2</sup> 9200 g/m <sup>2</sup>
<b>Construction</b>	EpuCore (patented composite base)			
<b>Surface</b>	regular wood embossed	light wood embossed	regular wood embossed	light wood embossed
<b>Finish</b>	EpuShield (anti-scratch matte coating)			
<b>Underlay</b>	pre-attached IXPE			
<b>Installation</b>	floating (click system under license from Valinge)			
<b>Warranty</b>	20 years residential 10 years commercial		25 years residential 10 years commercial	
<b>Pieces per box</b>	10 pcs	12 pcs	10 pcs	16 pcs
<b>Area per box</b>	2,20 m <sup>2</sup>	0,94 m <sup>2</sup>	2,20 m <sup>2</sup>	1,25 m <sup>2</sup>
<b>Weight per box</b>	18,5 kg	7,75 kg	21 kg	11,5 kg
<b>Fire resistance</b>	EN 13501-1		Bfl-s1	
<b>Formaldehyde emission</b>	EN 14041		E1	
<b>Slip resistance</b>	EN 13893 DIN 51130:2014		DS R10	
<b>Dimension stability</b>	EN 23999		norm: ≤ 0,25% ≤ 0,15%	
<b>Curling</b>	EN 23999		pass (≤ 2mm)	
<b>Wear group classification</b>	EN ISO 10874	23: domestic heavy 31: commercial moderate		23: domestic heavy 33: commercial heavy
<b>Abrasion resistance</b>	EN13329 Annex E	pass (≥ 1600 cycles)		pass (≥ 4000 cycles)
<b>Castor chair</b>	EN 425			pass (no visible change)
<b>Residual indentation</b>	EN 434			pass (≤ 0,1 mm)
<b>Stain resistance</b>	EN 438			pass (class 5)
<b>UV resistance</b>	ISO 105-B02			pass (≥ 6)
<b>Thermal conductivity</b>	EN 12524			0,09 W/mK
<b>Thermal resistance</b>	EN 12524			0,068 (m <sup>2</sup> K)/W
<b>Underfloor heating</b>		suitable for underfloor heating under certain conditions		
<b>Acoustic insulation</b>	EN ISO 717-2			ΔLw 19 dB

Multi-layer rigid vinyl flooring under VinCore brand come with the warranty. More details about the conditions can be found in the relevant warranty documents.  
Created based on declaration of performance DOP-2022/01 v. EN02.



**EPUFLOORING Sp. z o.o.**

Office: Kopcinskiego 77, 90-033 Lodz, Poland  
Warehouse: Ossendowskiego 3B, 93-228 Lodz, Poland  
dok.epuflooring@epufloor.com  
www.vincore.pl